

Sealing Compound PLAST 2000® || BN 150597



Content	70 cm ³	
Temperature resistance	-60 to +180 °C	
Operating temperature range, hardened	-40 to + 85 °C	
Storage temperature range, tube	+5°C to +25°C	
Storage period, sealed tube	unlimited, after 5 years a test of the usage properties is recommended	
Hardening time	14 days for approx. 10 mm	
Filling quantity approx.	cable type	per connector
	LF 1/2"-50	4 cm ³
	LF 5/8"-50	6 cm ³
	LF 7/8"-50	7 cm ³
	LF 1 1/4"-50	15 cm ³
	LF 1 5/8"-50	20 cm ³
	LF 2 1/4"-50	28 cm ³
	HCA58-50	5 cm ³
	HCA78-50	5 cm ³
	HCA118-50	10 cm ³
	HCA158-50	20 cm ³
	HCA295-50	50 cm ³
	HCA400-50	70 cm ³
	HCA495-50	120 cm ³
HCA550-50	250 cm ³	
HCA618-50	300 cm ³	
Weight, approx.	0.120 kg	
Scope of delivery	tube, tube squeezer, box (42 x 31 x 150 mm)	
Required accessory	Injection gun BN 070551	

Please visit www.spinner-group.com for material safety data sheet
 Also available: 20 cm³ tube BN 151671