


Precision Adaptor || BN 534907R000



**Radio frequency characteristics**

Interface type	2.92 mm plug / plug per IEEE Std 287 <sup>1)</sup>
Frequency range	DC to 44 GHz
Impedance	50 Ω
Return loss, min.	33 dB @ DC to 4 GHz 30 dB @ 4 to 26.5 GHz 25 dB @ 26.5 to 40 GHz 23 dB @ 40 to 44 GHz

1) In preparation of the upcoming new version of the IEEE Std. 287 the adaptor has a pin diameter of 0.927 mm. Usage with female connectors designed for a pin diameter of 0.914 mm results in an increase of the reflection factor magnitude of typically 0.02.

**Mechanical characteristics**

Center conductor material / surface finish	CuBe age hardened / gold-plated
Outer conductor material / surface finish	CuBe / gold-plated
Insulation	PS
Other metallic parts / surface finish	copper alloy / gold-plated CuBe / CuSnZn-plated
Weight, approx.	0.01 kg
Marking	laser engraving

**Environmental conditions**

<b>Operation</b>	
Ambient temperature range	+18 to +28°C
<b>Storage</b>	
Ambient temperature range	-40 to +70°C
Relative humidity, max.	95% (non condensing)

**Scope of delivery and accessories**

Scope of delivery	certificate of calibration, calibration data, handling instructions
-------------------	---

SPINNER GmbH  
This document is proprietary to us.  
All rights reserved. Any use, transfer, or reproduction of this document  
or the know-how contained therein requires our express consent.