

6 Port Patch Panels (UHF)

- 19" front panel
- Access to the interlock terminal strip provided at the front
- Symmetrical power splitter included
- U-links with interlock system 1 (IL 1-4) or 2 (2-10)
- Measurement at the front possible

Part Number	Interlock 1 Interlock 2	BN 553285C0100 BN 553282C0200	BN 553579C0100 BN 553576C0200
Frequency range		470 - 860 MHz	
Proof voltage		≤ 10 kV	≤ 13 kV
Average power		≤ 7 kW	≤ 17.5 kW
Insertion loss		≤ 0.15 dB	≤ 0.10 dB
VSWR		≤ 1.05	
Switching port size		1 5/8" USL-D	29.5-68 USL-D
Input / output connectors		1 5/8" EIA male	3 1/8" EIA
Number of interlock contacts		4/10	
Rating of the interlock contacts		Max. voltage ≤ 60.0 V DC ≤ 42.4 V ACpk Max. current ≤ 0.75 A / 0.1 A	
Phase accuracy of outputs		3°	
Dimensions (H x W x D) mm		444 x 483 x 260	488 x 483 x 260
Weight		≈ 25 kg	≈ 34 kg
Rack		No	
Environmental conditions		For limitations see „Environmental Conditions for Broadcast Products“.	
Accessories			
Measurement adapters		See U-links and measurement adapters.	

