





Band 3 DAB Starpoint Combiners

- Compact design as 19" slide-in unit
- For 1.54 MHz block width
- Integrated mask filters for DAB and T-DMB
- Temperature compensated



Part Number	BN 576851C0001 2 Inputs	BN 576847C0001 3 Inputs	BN 576848C0001 4 Inputs
Frequency range		174 - 240 MHz	
Block Spacing		≥ 1	
Narrowband input		7-16 female	
Filter type integrated		6/70 ≡ BN 617149	
Temperatur stability		$\leq 1 \text{ kHz} / \text{K}$	
Harmonics attenuation		$\geq 50 \text{ dB}$ for $f \leq 500 \text{ MHz}$	
Standard		DAB / T-DMB @ 1.54 MHz / ($\hat{U}/U_{\text{rms}}=13 \text{ dB}$)	
Average input power		300 W per input	
Channel spacing		≥ 1	
Tuning instruction		AS6600	
Insertion loss and mask filtering		174 MHz 240 MHz f_0 $\leq 1.35 \text{ dB}$ $\leq 1.60 \text{ dB}$ $f_0 \pm 0.77$ $\leq 3.60 \text{ dB}$ $\leq 4.10 \text{ dB}$ $f_0 \pm 0.97$ $\geq 15 \text{ dB}$ $f_0 \pm 1.75$ $\geq 45 \text{ dB}$ $f_0 \pm 2.20$ $\geq 50 \text{ dB}$ $f_0 \pm 3.00$ $\geq 55 \text{ dB}$	
Group delay variation		$\Delta\tau \leq 1200 \text{ ns}$	
Output		7-16 female	
Isolation between inputs		$\geq 35 \text{ dB}$	
VSWR		≤ 1.2	
Dimensions (L x W x H) mm	611 x 484 x 200	611 x 484 x 305	611 x 484 x 415
Weight	$\approx 43 \text{ kg}$	$\approx 62 \text{ kg}$	$\approx 82 \text{ kg}$
Environmental conditions	For limitations see „Environmental Conditions for Broadcast Products“.		