


Rotary Joint || BN 153168



Radio frequency characteristics

Channel designation	Inner channel (CH1)	Outer channel (CH2)
Interface type / material / surface finish	SMA-f (50 Ω) / copper alloy / gold plated	SMA-f (50 Ω) / copper alloy / gold plated
Interface orientation	style I	style I
Frequency range	DC to 8 GHz	DC to 8 GHz
Peak power capability	1 kW	1 kW
Average power capability	100 W @ DC to 2 GHz 60 W @ 2 to 4 GHz 35 W @ 4 to 8 GHz	10 W
VSWR, max.	1.35 @ DC to 8 GHz	2.0 @ DC to 4 GHz 2.5 @ 4 to 8 GHz
VSWR variation over rotation, max.	0.1	0.1 @ DC to 4 GHz 0.4 @ 4 to 8 GHz
Insertion loss, max.	0.4 dB	0.5 dB @ DC to 4 GHz 1.0 dB @ 4 to 8 GHz
Insertion loss variation over rotation, max.	0.06 dB	0.1 dB @ DC to 4 GHz 0.35 dB @ 4 to 8 GHz
Phase variation over rotation, max.	0.5 deg.	4 deg.
Isolation, min.	50 dB	
DC carrying capability	0.5 A, 48 VDC @ full RF avg. power 2 A, 48 VDC @ RF avg. power 5 W 5 A*, 48 VDC @ RF avg. power 5 W	0.5 A, 24 VDC @ full RF avg. power

Conditions:

DC applied to one channel only

* applied for max. 1 x 10E6 revolutions or 50 h

Rotary Joint || BN 153168

Mechanical characteristics

Rotating speed, max. / nominal	60 / 30 rpm
Life, min.	5 x 10 ⁶ revolutions
Torque (room / min. temperature), max.	0.05 Nm / - @ start-up 0.05 Nm / - @ rotation
Interface loads, max.	±5 N in axial direction ±5 N in radial direction
Case material	aluminum alloy
Case surface finish	chromate conversion coat per MIL-DTL-5541 type 1 or type 2
IP protection level	IP64
Weight, approx.	0.13 kg
Marking	adhesive label

Environmental conditions

Operation	
Ambient temperature range	-40 to +71°C
Relative humidity, max.	95% (non-condensing)
Storage	
Ambient temperature range	-55 to +85°C
Relative humidity, max.	95% (non-condensing)

Applicable Documents

Drawing	153168-0E Issue C
Technical information	"Rotary Joints – Glossary", Technical Document TD-00021, Spinner GmbH