



X ( 15:1 )

Y ( 30 : 1 )

**Note:**

This layout is optimized for high frequency laminate type RO3003, thickness 0.127 mm, 17 $\mu$ m electrodeposited copper foil on both sides.  
 Suitable for all types of PCB-Launch-Connectors SPINNER *EasyLaunch*

Allgemeintoleranzen / General tolerances <b>DIN ISO 2768 mH</b>		Datum Date	Name Name	Teile-Nr. / Part-No. <b>A96165</b>	Oberfläche / Surface
Maßangaben in mm Dimensions in mm	DIN ISO 128-30: 	Erstellt Creator	05.04.2016 Grabichler	Bezeichnung / Title <b>Printed Circuit Board</b>	
		Geprüft Checked	04.07.2024 Niebauer	printed circuit board for Launch Connec	
		Rev. Rev.	Änd.-Nr. Issue-No.	Datum Date	Name Name
		D	Editorial	04.07.24	Niebauer
		C	div.Änd.	21.08.18	Grabichler
		B	div.Änd.	09.05.18	Niebauer
		Dokumentart / Doc. category <b>Outline Drawing</b>		Sprache / Language <b>EN</b>	
		Dokument-Nr. / Document-No. <b>A96165-0E</b>		Dok.-Rev. / Doc-Rev. <b>D</b>	Format / Format <b>A3</b>
		Maßstab / Scale <b>10 : 1</b>		Blatt / Sheet <b>1/1</b>	



SPINNER GmbH  
 Erzgiesserei Str. 33  
 D-80335 München  
 spinner-group.com