

3 Port Patch Panels

- 19" front panel
- Access to the interlock terminal strip provided at the front
- Slim design panels with minimum height are supplied with loose interlock terminal strip
- U-links with interlock system 1 (IL 1-4)
- Measurement at the front possible

Part Number		BN 547171C0110 Standard BN 547171C0101 Slim Design	BN 554175 Standard BN 554175C0101 Slim Design	BN 553431C0100 Standard BN 553431C0101 Slim Design
Frequency range		0 - 860 MHz		
Proof voltage		≤ 2.7 kV	≤ 10 kV	≤ 13 kV
Average power	100 MHz 240 MHz 860 MHz	≤ 5.0 kW ≤ 3.5 kW ≤ 2.0 kW	≤ 20.0 kW ≤ 13.5 kW ≤ 7.0 kW	≤ 51.0 kW ≤ 34.0 kW ≤ 17.5 kW
Insertion loss		≤ 0.1 dB		
VSWR		≤ 1.04		
Switching port size		7-16 female	1 5/8" USL-D	29.5-68 USL-D
Input / output connectors		7-16 female	1 5/8" EIA male	3 1/8" EIA
Number of interlock contacts		4		
Rating of the interlock contacts Max. voltage Max. current		≤ 60.0 V DC ≤ 42.4 V ACpk ≤ 0.75 A		
Dimensions (H x W x D) mm		BN 547171C0110 177 x 483 x 35	BN 554175 309 x 483 x 65	BN 553431C0100 444 x 483 x 115
		BN 547171C0101 132 x 483 x 15	BN 554175C0101 177 x 483 x 65	BN 553431C0101 266 x 483 x 115
Weight		≈ 3.6 kg	≈ 6.0 kg	≈ 9.6 kg
Rack		No		
Environmental conditions		For limitations see „Environmental Conditions for Broadcast Products“.		
Accessories				
Measurement adapters		See U-links and measurement adapters.		

