

Single Channel Rotary Joint || BN 635726



Outline and dimensions as per drawing 635726-0E

**Radio frequency channel characteristics**

Channel designation	Channel 1
Interface type / material / surface finish	Compatible with UBR120 (IEC-154) See 635726-0E / aluminum alloy
Interface orientation	style L
Frequency range	13.75 to 14.5 GHz
Peak power capability	8 kW @ sea level <sup>RF1)</sup>
Average power capability	750 W <sup>RF1)</sup>
VSWR, max. / typ.	1.2 / 1.1
VSWR variation over rotation, max. / typ.	0.1 / 0.05
Insertion loss, max. / typ.	0.2 dB / 0.1 dB
Insertion loss variation over rotation, max. / typ.	0.05 dB / 0.02 dB

<sup>RF1)</sup> Conditions: 300 W @ 16800 m operating altitude

**General mechanical data**

Rotating speed, max.	150 rpm
Differential operating pressure, max. / nominal	0.2 MPa (2 bar) / 0.1 MPa (1 bar)
Leakage rate, max.	10 cm <sup>3</sup> / minute @ nominal differential pressure
Life, min.	20 x 10 <sup>6</sup> revolutions
Torque (room temperature), max.	0.50 Nm
Case material	Aluminum alloy
Case surface finish	Chromate conversion coat per MIL-C-5541
Weight, approx.	0.35 kg
Marking	Adhesive label

## Single Channel Rotary Joint || BN 635726

**General environmental conditions**

<b>Operation</b>	
Ambient temperature range	-40 to +71 °C
Relative humidity, max.	95% (non-condensing)
IP protection level	IP65 per EN 60529 (all interfaces mated with sealed flanges)
<b>Storage</b>	
Ambient temperature range	-55 to +85 °C
Relative humidity, max.	95% (non-condensing)