


Precision Open || BN 535523R000



Radio frequency characteristics ¹⁾

Interface type	1.5-3.5 plug
Frequency range	DC to 13 GHz
Impedance	50 Ω
Phase deviation, max.	1.5 deg. @ DC to 4 GHz
	3 deg. @ 4 to 8 GHz
	4.5 deg. @ 8 to 13 GHz

Mechanical characteristics

Center conductor material / surface finish	CuBe age hardened / gold-plated
Outer conductor material / surface finish	copper alloy / gold-plated copper alloy / CuSnZn-plated
Insulation	cross linked polystyrene
Other metallic parts / surface finish	copper alloy / nickel-plated
Weight, approx.	22 g
Marking	laser engraving

Environmental conditions

Operation	
Ambient temperature range	+5 to +40°C
Storage	
Ambient temperature range	-40 to +70°C
Relative humidity	95% (non-condensing)

Scope of delivery and accessories

Scope of delivery	certificate of calibration, calibration data, handling instructions, protective cap
-------------------	---

¹⁾ The specifications for the open are given as allowed deviation from the nominal model as defined in the calibration data. Calibration data in formats for the common VNAs are included in the delivery. It includes offset length and individual calibration coefficients to achieve the best possible performance.

SPINNER GmbH
 This document is proprietary to us.
 All rights reserved. Any use, transfer, or reproduction of this document
 or the know-how contained therein requires our express consent.