6 Port Patch Panels (UHF)

- Open rack
- Access to the interlock terminal strip provided at the front
- Symmetrical power splitter included
- U-links with interlock system 2 (IL 2-10)
- Measurement at the front possible

Part Number	BN 553881A0200	BN 540642A0200	BN 540652A0200	BN 540643A0200
Frequency range	470 - 860 MHz			
Proof voltage	≤ 19 kV	≤ 23 kV	≤ 25 kV	
Average power	≤ 35 kW	≤ 47 kW	≤ 60 kW	≤ 80 kW (800 MHz)
Insertion loss	≤ 0.1 dB			≤ 0.05 dB
VSWR	≤ 1.05			
Switching port size	43-98 USL-D	52-120 USL		6 1/8" USL
Input / Output connectors	4 1/2" EIA male 339 IEC 50-105	6 1/8" EIA		
Number of interlock contacts	10			
Rating of the interlock contacts Max. voltage Max. current	≤ 60.0 V DC ≤ 42.4 V ACpk ≤ 0.1 A			
Phase accuracy of outputs	3°			
Dimensions (H x W x D) mm	1980 x 790 x 900	1980 x 990 x 900		1980 x 1190 x 900
Weight	≈ 145 kg	≈ 180 kg		≈ 215 kg
Rack	Yes			
Environmental conditions	For limitations see „Environmental Conditions for Broadcast Products“.			
Accessories				
Measurement adapters	See U-links and measurement adapters.