

4 Port Patch Panels

- 19" front panel
- Access to the interlock terminal strip provided at the front
- Slim design panels with minimum height are supplied with loose interlock terminal strip
- U-links with interlock system 1 (IL 1-4)
- Measurement at the front possible

Part Number		BN 547174 Standard BN 547174C0101 Slim Design	BN 554174 Standard BN 554174C0101 Slim Design
Frequency range		0 - 860 MHz	
Proof voltage		≤ 2.7 kV	≤ 10 kV
Average power	100 MHz 240 MHz 860 MHz	≤ 5.0 kW ≤ 3.5 kW ≤ 2.0 kW	≤ 20.0 kW ≤ 13.5 kW ≤ 7.0 kW
Insertion loss		≤ 0.1 dB	
VSWR		≤ 1.04	
Switching port size		7-16 female	1 5/8" USL-D
Input / output connectors		7-16 female	1 5/8" EIA male
Number of interlock contacts		4	
Rating of the interlock contacts		Max. voltage ≤ 60.0 V DC ≤ 42.4 V ACpk Max. current ≤ 0.75 A	
Dimensions (H x W x D) mm		BN 547174 310 x 483 x 35 BN 547174C0101 221 x 483 x 15	BN 554174 444 x 483 x 65 BN 554174C0101 310 x 483 x 65
Weight		≈ 4.6 kg	≈ 8.5 kg
Rack		No	
Environmental conditions		For limitations see „Environmental Conditions for Broadcast Products“.	
Accessories			
Measurement adapters		See U-links and measurement adapters.	

