

## 6 Port Patch Panels (VHF)

- 19" front panel
- Access to the interlock terminal strip provided at the front
- Symmetrical power splitter included
- U-links with interlock system 1 (IL 1-4) or 2 (IL 2-10)
- Measurement at the front possible

Part Number	BN 553284	BN 554343	BN 554507
Frequency range	170 - 240 MHz		
Proof voltage	≤ 10 kV	≤ 13 kV	≤ 18 kV
Average power	≤ 13.5 kW	≤ 34 kW	≤ 48 kW
Insertion loss	≤ 0.1 dB		
VSWR	≤ 1.05		
Switching port size	1 5/8" USL-D	29.5-68 USL-D	43 – 98 USLD
Input / output connectors	1 5/8" EIA male	3 1/8" EIA	4 1/2" EIA male 339 IEC 50-105
Number of interlock contacts	4		10
Rating of the interlock contacts Max. voltage	≤ 60.0 V DC ≤ 42.4 V ACpk		
Max. current	≤ 0.75 A		≤ 0.1 A
Phase accuracy of outputs	3°		
Dimensions (H x W x D) mm	444 x 483 x 264		1980 x 790 x 900
Weight	≈ 25 kg	≈ 34 kg	≈ 150 kg
Rack	No		Yes
Environmental conditions	For limitations see „Environmental Conditions for Broadcast Products“.		
<b>Accessories</b>			
Measurement adapters	See U-links and measurement adapters.		

